

## Specification

- 6mm bucket shell and sides
- Double folded leading edge
- 400 Brinell edge as standard
- Brackets to suit your machine
- Boxed top edge for added strength



## Technical Data

Width	Capacity Cubic Feet	Capacity Cubic Meters	Height	Depth	Weight
5'0" (1.52m)	25	0.71	35"	43"	324 kgs
6'0" (1.83m)	22	0.62	30"	37"	289 kgs
6'0" (1.83m)	30	0.85	35"	43"	361 kgs
6'6" (2.00m)	24	0.68	30"	37"	307 kgs
6'6" (2.00m)	32	0.92	35"	43"	380 kgs
6'6" (2.00m)	43	1.22	38"	53"	494 kgs
7'0" (2.13m)	26	0.74	30"	37"	319 kgs
7'0" (2.13m)	35	0.99	35"	43"	397 kgs
7'0" (2.13m)	47	1.33	38"	53"	509 kgs
7'6" (2.31m)	28	0.79	30"	37"	337 kgs
7'6" (2.31m)	38	1.08	35"	43"	420 kgs
7'6" (2.31m)	50	1.41	38"	53"	533 kgs
7'6" (2.31m)	70	1.98	45"	62"	643 kgs
8'0" (2.46m)	40	1.13	35"	43"	434 kgs
8'0" (2.46m)	53	1.50	38"	53"	556 kgs
8'0" (2.46m)	75	2.12	45"	62"	669 kgs
8'0" (2.46m)	100	2.83	50"	71"	829 kgs
8'6" (2.62m)	106	3.02	50"	71"	855 kgs
8'6" (2.62m)	132	3.74	57"	78"	987 kgs
9'0" (2.75m)	140	3.97	57"	78"	1,028 kgs